



OR-BXK-HS

Three Phase Hybrid Inverter

4.0KW/5.0KW/6.0KW/8.0KW/10.0KW/12.0KW



Big LCD display



Power export limit



Compact and easy to install



Wifi/GPRS/Lan communication optional



Simpler

Quick and easy single person installation
Fault codes warning view on LCD display
Built-in limiter optional



Safer

comply with international quality standards
tested by TUV,BV,Dekra etc.



Great reliability

IP65 ingress protection
10+years R&D accumulation and support

ANYTIME, ANYWHERE

REMOTE MONITORING PLATFORM

Monitor system performance in
real-time via smartphone app or
web portal using out advanced
monitoring platform .



OR-BXK-HS Three Phase



For more about OR-BXK-HS grid tie inverter
please visit www.oreesolar.com

www.oreesolar.com

THREE PHASE HYBRID INVERTER

Technology Data

EPH Series EPH10KTL (4KW / 5KW / 6KW / 8KW / 10KW / 12KW)

Model No	OR-BXK-HS-4KW	OR-BXK-HS-5KW	OR-BXK-HS-6KW	OR-BXK-HS-8KW	OR-BXK-HS-10KW	OR-BXK-HS-12KW
Input (DC)						
Max DC power	6000W	7500W	9000W	12000W	15000W	15000W
Max DC voltage	1000Vd.c.					
MPPT voltage range	200...850Vd.c.					
Max input current/per string	13A/13A					
Number of MPP trackers	2					
Strings per MPP tracker	1					
Battery Input						
Battery Type	Li-Ion					
Battery voltage range	130-700V					
Maximum charge/discharge current	25/25A					
Charge strategy for Li-ion Battery	Self-adaptation to BMS					
Output (AC)						
AC nominal power	4000VA	5000VA	6000VA	8000VA	10000VA	12000VA
Max AC apparent power	5000VA	5500VA	7000VA	8800VA	11000VA	13200VA
Max output current	8A	10A	12A	15A	17A	20A
Nominal AC output	50/60Hz; 400/350					
AC output range	45/55Hz;280~490Vac(Adj)					
Power factor	0.8leading...0.8lagging					
Harmonics factor	<3%					
Grid type	3W/N/PE					
Three-phase unbalance output	0~100%	0~100%	0~100%	0~100%	0~100%	0~80%
AC Output (Back-up)						
Max AC apparent power	4000VA	5000VA	6000VA	8000VA	10000VA	10000VA
Norminal Output Voltage	400/380V					
Norminal Output Frequency	50/60HZ					
Output THDV (@Linear Load)	<3%					
Efficiency						
Maximum conversion efficiency	98.0%	98.0%	98.2%	98.2%	98.2%	98.2%
European efficiency	97.3%	97.3%	97.5%	97.5%	97.5%	97.5%
Max battery to AC Efficiency	97.2%	97.2%	97.4%	97.4%	97.4%	97.4%
MPPT efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
Safety and Protection						
DC reverse-polarity protection	yes					
DC breaker	yes					
DC/AC SPD	yes					
Leakage current protection	yes					
Insulation Impedance Detection	yes					
Residual Current protection	yes					
Output short circuit protection	yes					
Battery reverse connection protection	yes					
General Parameters						
Dimension (W/H/D)	548*444*184mm					
Weight	27 kg					
Operating temperature range °C	-25°C...+60 °C					
Degree of protection	IP65					
Cooling concept	Natural convection					
Topology	Transformerless					
Display	LCD					
Humidity	0-95%,no condensation					
Communication	Standard WiFi;GPRS/LAN(optional)					
Warranty	Standard 5 years; 7/10 years optional					
BMS communication	CAN/RS485					
Meter communication	RS485					
Certificates and Approvals						
CQC, VDE-AR-N4105,IEC61727, IEC62116, VDE0124-AR-N0124, EN50549, IEC62109, IEC62477						